

4.6 **Momenti d' inerzia [Kg.cm²]**
(riferiti all'albero veloce in entrata)

4.6 **Moments of inertia [Kg.cm²]**
(referred to input shaft)


4.6 **Trägheitsmoment [Kg.cm²]**
(bez. Antriebswelle)

H40	i _n	HA	HF	
			B5 - B14	
			IEC 56	IEC 63
30	0.080	0.125	0.125	
40	0.079	0.123	0.124	
60	0.077	0.122	0.123	
80	0.076	0.120	0.121	
100	0.075	0.120	0.120	
120	0.077	0.121	0.122	
160	0.075	0.120	0.120	
200	0.075	0.120	0.120	
260	0.074	0.119	0.119	
320	0.074	0.119	0.119	
400	0.074	0.119	0.119	

H50	i _n	HA	HF		
			B5	B5 - B14	
			IEC 56	IEC 63	IEC 71
30	0.161	0.208	0.366	0.383	
40	0.156	0.203	0.361	0.377	
60	0.152	0.199	0.357	0.374	
80	0.148	0.194	0.352	0.369	
100	0.147	0.194	0.352	0.368	
120	0.150	0.197	0.355	0.372	
160	0.146	0.193	0.351	0.368	
200	0.141	0.188	0.346	0.363	
260	0.138	0.185	0.343	0.360	
320	0.138	0.185	0.343	0.360	
400	0.138	0.185	0.343	0.360	

H63	i _n	HA	HF		
			B5	B5 - B14	
			IEC 63	IEC 71	IEC 80
30	0.405	0.639	0.656	1.219	
40	0.392	0.626	0.643	1.206	
60	0.383	0.617	0.634	1.197	
80	0.364	0.598	0.615	1.178	
100	0.362	0.596	0.613	1.176	
120	0.377	0.612	0.628	1.191	
160	0.361	0.595	0.612	1.175	
200	0.360	0.595	0.611	1.175	
260	0.354	0.588	0.605	1.168	
320	0.354	0.588	0.605	1.168	
400	0.354	0.588	0.605	1.168	



H75	i _n	HA	HF		
			B5	B5 - B14	
			IEC 71	IEC 80	IEC 90
30	0.865	1.643	1.778	2.855	
40	0.835	1.613	1.748	2.825	
60	0.813	1.592	1.726	2.804	
80	0.777	1.556	1.690	2.768	
100	0.773	1.551	1.686	2.764	
120	0.801	1.579	1.714	2.791	
160	0.770	1.548	1.683	2.760	
200	0.769	1.547	1.682	2.759	
260	0.751	1.530	1.664	2.742	
320	0.751	1.530	1.664	2.742	
400	0.751	1.529	1.664	2.742	







4.6 **Momenti d' inerzia** [Kg.cm²]
(riferiti all'albero veloce in entrata)

4.6 **Moments of inertia** [Kg.cm²]
(referred to input shaft)

4.6 **Trägheitsmoment** [Kg.cm²]
(bez. Antriebswelle)

H90	i_n	HA 	HF 		
			B5		B5 - B14
			IEC 71	IEC 80	IEC 90
30	1.064	1.843	1.977	3.055	
40	1.000	1.779	1.913	2.991	
60	0.955	1.733	1.868	2.945	
80	0.845	1.623	1.758	2.835	
100	0.836	1.615	1.749	2.827	
120	0.927	1.706	1.840	2.918	
160	0.829	1.608	1.742	2.820	
200	0.827	1.606	1.740	2.818	
260	0.784	1.562	1.696	2.774	
320	0.783	1.562	1.696	2.774	
400	0.783	1.561	1.695	2.773	

H110	i_n	HA 	HF 		
			B5		B5 - B14
			IEC 80	IEC 90	IEC 110-112
30	2.558	4.726	4.654	6.424	
40	2.379	4.547	4.475	6.246	
60	2.251	4.420	4.347	6.118	
80	1.958	4.127	4.054	5.825	
100	1.933	4.102	4.029	5.800	
120	2.175	4.343	4.271	6.041	
160	1.915	4.084	4.011	5.782	
200	1.909	4.077	4.005	5.776	
260	1.779	3.948	3.875	5.646	
320	1.778	3.946	3.874	5.645	
400	1.777	3.945	3.873	5.644	

H130	i_n	HA 	HF 		
			B5		
			IEC 80	IEC 90	IEC 110-112
30	5.64	7.90	10.22	11.83	
40	5.15	7.42	9.73	11.35	
60	4.81	7.07	9.39	11.00	
80	4.15	6.41	8.72	10.34	
100	4.07	6.34	8.65	10.27	
120	4.60	6.86	9.18	10.79	
160	4.03	6.29	8.61	10.22	
200	4.01	6.27	8.59	10.20	
260	3.75	6.01	8.32	9.94	
320	3.74	6.00	8.32	9.93	
400	3.74	6.00	8.32	9.93	