







4.7 **Momenti d'inerzia** [Kg.cm<sup>2</sup>]  
(riferiti all'albero veloce in entrata)



4.7 **Moments of inertia** [Kg.cm<sup>2</sup>]  
(referred to input shaft)


4.7 **Trägheitsmoment** [Kg.cm<sup>2</sup>]  
(bez. Antriebswelle)



<b>63A</b>	$i_n$	 PA
	5	1.09
	6.3	0.86
	8	0.62


<b>63B</b>	$i_n$	 PA	 PC				
			IEC B5				
			<b>63</b>	<b>71</b>	<b>80</b>	<b>90</b>	
			10	0.87	1.01	1.38	1.43
			12.5	0.81	0.95	1.33	1.38
			16	0.77	0.92	1.30	1.35
			20	0.40	0.54	0.92	0.97
			25	0.39	0.53	0.91	0.95
31.5	0.30	0.38	0.52	0.90	0.95		
40	0.30	0.37	0.51	0.89	0.94		



<b>80A</b>	$i_n$	 PA
	5	3.45
	6.3	2.60
	8	1.87


<b>80B</b>	$i_n$	 PA	 PC					
			IEC B5					
			<b>71</b>	<b>80</b>	<b>90</b>	<b>100-112</b>		
			10	2.94	3.40	3.57	3.95	4.79
			12.5	2.77	3.23	3.40	3.77	4.61
			16	2.65	3.11	3.28	3.66	4.49
			20	1.22	1.68	1.85	2.23	3.07
			25	0.95	1.45	1.62	1.99	2.83
			31.5	0.91	1.42	1.59	1.96	2.80
			40	0.89	1.39	1.56	1.94	2.78
50	0.88	1.38	1.55	1.93	2.76			
63	0.63	1.16	1.33	1.71	2.55			



<b>100A</b>	$i_n$	 PA
	5	10.09
	6.3	7.40
	8	5.26

<b>100B</b>	$i_n$	 PA	 PC					
			IEC B5					
			<b>80</b>	<b>90</b>	<b>100-112</b>	<b>132</b>		
			10	9.58	11.01	10.88	11.83	14.97
			12.5	8.72	10.15	10.02	10.98	14.12
			16	8.32	9.75	9.62	10.57	13.71
			20	3.91	5.08	4.95	5.90	9.04
			25	3.04	4.27	4.14	5.10	8.24
			31.5	2.89	4.12	3.99	4.95	8.09
			40	2.82	4.05	3.92	4.88	8.02
50	2.77	4.00	3.87	4.83	7.97			
63	1.95	3.28	3.15	4.11	7.24			

<b>125A</b>	$i_n$	 PA
	5	28.98
	6.3	22.22
	8	15.91

<b>125B</b>	$i_n$	 PA	 PC							
			IEC B5							
			<b>80</b>	<b>90</b>	<b>100-112</b>	<b>132</b>	<b>160</b>	<b>180</b>		
			10	28.02	29.78	29.65	29.79	32.99	37.41	40.43
			12.5	25.22	26.98	26.85	26.98	30.18	34.61	37.63
			16	24.17	25.93	25.80	25.94	29.14	33.56	36.58
			20	11.08	12.52	12.39	12.53	15.73	20.15	23.17
			25	8.65	10.19	10.06	10.20	13.40	17.83	20.84
			31.5	8.16	9.70	9.57	9.71	12.91	17.34	20.35
			40	7.98	9.52	9.39	9.53	12.73	17.15	20.17
50	7.83	9.37	9.24	9.38	12.58	17.01	20.02			
63	5.42	7.28	7.16	7.29	10.49	14.92	17.94			

<b>160A</b>	$i_n$	 PA
	5	93.17

<b>125B</b>	$i_n$	 PA	 PC						
			IEC B5						
			<b>110-112</b>	<b>132</b>	<b>160</b>	<b>180</b>	<b>200</b>		
			10	87.64	91.32	97.00	96.00	98.91	109.30
			12.5	78.05	81.74	87.42	86.42	89.33	99.72
			16	75.36	79.04	84.72	83.72	86.63	97.02
			20	34.51	37.42	43.10	42.10	45.01	55.40
			25	27.20	30.18	35.86	34.86	37.77	48.16
			31.5	25.53	28.51	34.19	33.19	36.10	46.49
			40	25.06	28.03	33.72	32.72	35.63	46.01
50	24.52	27.50	33.18	32.18	35.09	45.48			
63	17.07	20.98	26.67	25.66	28.57	38.96			